

CERAMIC NANO SHAMPOO

impurity remover, shampoo (150 ml)

Instructions for use:

Shake well before use. The recommended dilution ratio is 1 : 300. That means approximately 30ml of shampoo per 10l of clean water.

If the bodywork is quite clean it is possible to use a lower concentration – 15ml per 10l of water. On the other hand if the bodywork is heavily soiled it is possible to use a stronger concentration of up to 1 : 30. Mix water with the shampoo and leave it to stand for about 2 minutes. Using a soft sponge, clean the bodywork with circular motions. Do not forget that the better you clean the surface the better the adhesive properties and service life of the subsequent polish will be! In cases of extremely dirty bodywork do not hesitate to wash your car two or more times.

CAUTION – the most frequent reason for failures in application is when the surface that has not been properly degreased! The use of greasy preparations, such as clay or similar, or a preliminary washing of the car in an automatic car wash (where waste water with spray wax is usually recycled) may reduce the effect and shorten the service life of PIKATEC polish. Also air compressors, used to dry the car body, sometimes exude oil, which is used to lubricate the compressor's piston, along with the air – this is often the case unless the compressor is equipped with a filter.

Do not apply under direct sunlight!

Watch video instructions at www.pikatec.cz or you can use the QR code.